



micnode aux

Expansion unit for micnode2

The micnode aux is a convenient and cost-efficient tool to provide paging at a secondary location close to the main micnode2 unit. It is connected to the micnode2 using a single CAT5 cable which carries audio, data and power.

Description	Expansion unit for micnode2
Connectivity	1 x RJ 45 input for connecting a dynamic microphone 1 x RJ45 for connecting to micnode2 aux port
User Interface	Status LED 3 x Zone select button with indicator LED's
Compatibility	micnode2
Environmental	Operating temperature range 32 °F – 122 °F (0 °C – +50 °C) Storage temperature range 14 °F to 140 °F (-10 °C – +60 °C)
Power	12V sourced from micnode2
Dimensions	111 mm (W) x 42 mm (D) x 107 mm (H) US 2-gang box compatible 400 g without Microphone
Accessories	Mounting kit, Microphone, Desk stand (optional)

key features

- Expansion unit for micnode2
- Three zone selection buttons and status LEDs
- Built-in high-quality preamplifier
- Connected using single CAT5 cable
- Up to 100 meters from micnode2
- 2-gang box compatible



nnounce™ by Simpleway

Simpleway Europe a.s., Na Okraji 335/42, 162 00 Prague, Czech Republic,
Simpleway Inc., 1621 Central Avenue, 82001 Cheyenne, Wyoming, USA

✉ customer@simpleway.global 🌐 www.nnounce.com 📺 simplewayglobal

